

Customer: SELDEN MID EUROPE
 Sales manager: Pieter Oenema
 Date created: 13-08-26
 Latest revision: 14-01-30
 Approved: 14-01-30 by AJ

Test production only

General rig description

Conventional Fractional
 Keelstepped 2-spreader
 Tapered Sloop

Rig dimensions

Forestay height FH: 18.870 mm
 Cutterstay height CS: 13.600 mm
 Main sail luff length P: 18.501 mm
 Boom height above deck BH: 1.171 mm
 Bury Q: 2.265 mm
 Main sail foot length E: 5.986 mm
 Main boom sheet pos S: 4.800 mm
 Foretriangle width J: 5.222 mm
 Spinnaker pole length SPL: 5.222 mm

Chainplates dist. from cl mast

	Lateral	Long	
Cap shrouds:	1765	385 mm	(12,3°)
Aft lowers:	1765	470 mm	
Deck above chainplates:	330 mm		
Deck above waterline:	1710 mm		

Hull and righting moment

Equipped boat
 Designers RM: 103,5 kNm @30°

Spar sections

Mast: C304
 Boom: B250
 Spin. pole: S111 Carbon: SC119

Top spinnaker/gennaker OK
 Max code zero height: 19860 (990mm above FH)
 2:1 purchase system for code zero halyard

Furlex

Forestay: 412 Cutterstay: 310

Notes (4 lines)

Cutterstay with runners optional.

Runners (CS) and upper spreaders may be in contact during sailing.

